

**BRIDGEMAN**

**MODULAR  
SAFE  
DEPOSIT  
BOXES**



# Bridgeman Modular Case Safe Deposit Box Series.

**Advanced design, rugged construction, improved security.**

Today's new standard in safe deposit boxes has been developed by Bridgeman Security Equipment...the innovative company specializing in institutional security since 1955.

Through the use of rugged aluminum construction and maintenance-free finishes, Bridgeman's modular case safe deposit box series offer attractive, low cost modular construction, and minimal upkeep.


## Construction

The Bridgeman series of safe deposit boxes combines sturdy aluminum alloy doors and frames with cabinets of rust-resistant steel. For high security, the die-cast doors are engineered with a continuous heavy flange which interlocks with the door jamb. Both attractive finishes provide a virtually maintenance-free vault.


The modular cabinets are dimpled for a positive interlock when stacked in sections, and are designed for easy installation. The Bridgeman series may be installed flush against the vault wall, utilizing every inch of valuable wall space.

# SD and SS Series


Outside dimensions: 16" High, 32 5/8" Wide, 24" Deep.




SD 42 (Wt. 270 lbs.)  
42 openings ea. 2" x 5"




SD or SS 9 (Wt. 149 lbs.)  
3 openings ea. 3" x 10" and 6 openings ea. 6" x 10"




SD or SS 30 (Wt. 230 lbs.)  
30 openings ea. 3" x 5"



SD or SS 9A (Wt. 149 lbs.)  
9 openings ea. 5" x 10"




SD or SS 18 (Wt. 176 lbs.)  
18 openings ea. 5" x 5"



SD or SS 6 (Wt. 132 lbs.)  
3 openings ea. 6" x 10" and 3 openings ea. 9" x 10"




SD or SS 15 (Wt. 180 lbs.)  
15 openings ea. 3" x 10"




SD or SS 6A (Wt. 132 lbs.)  
3 openings ea. 5" x 10" and 3 openings ea. 10" x 10"



SD or SS Base (Wt. 27 lbs.)



SD or SS 3 (Wt. 126 lbs.)  
3 openings ea. 15" x 10"





The SD and SN series are finished in an attractive reverse hammertone silver enamel, providing a virtually maintenance-free finish. Beige and bronze finishes are also available as options.



The SS and ST series have a satin finish stainless steel plate bonded into a recess in the high pressure diecast solid aluminum door cast at 25,000 p.s.i. The outside rim of the door and the diecast aluminum frame are finished in a matte black enamel, providing a virtually maintenance-free finish.



## Locks

Doors are fitted with a double nose, fixed lever lock, as listed by Underwriters Laboratory. The lock features an eleven lever construction (five guard, six customer) for optimal resistance against forced entry. The possibility of over one million key changes and a strict security control system are combined to avoid duplication. Locks are firmly attached to doors at four points to aid in preventing punching.

## Number Plates

Glare-proof, matte finish plastic number plates are recessed into the face of each door. Plates may be easily interchanged at a later date, if the numbering sequence is changed.

## Key Tags

Attractive imprinted plastic tags with key rings are available at additional cost. Standard procedure provides two customer keys in sealed, numbered envelopes.

## Bases


Constructed of heavy duty tubular steel and finished to match the boxes. Standard bases are 3" high. Please specify if optional 3 1/2" height is required. Two separate widths to accommodate SD/SS or SN/ST modules are available.

## Bond Boxes

Metal bond boxes are furnished in all sizes. Boxes are constructed from sheet metal and finished in a grey bonderized enamel.

# SN and ST Series


Outside dimensions: 16" High, 10 7/8" Wide, 24" Deep.




SN 14 (Wt. 92 lbs.)  
14 openings ea. 2" x 5"




SN or ST 5 (Wt. 72 lbs.)  
5 openings ea. 3" x 10"




SN or ST 2 (Wt. 55 lbs.)  
1 opening ea. 6" x 10",  
1 opening ea. 9" x 10"




SN or ST 10 (Wt. 81 lbs.)  
10 openings ea. 3" x 5"




SN or ST 3 (Wt. 61 lbs.)  
1 opening ea. 3" x 10",  
2 openings ea. 6" x 10"




SN or ST 2A (Wt. 55 lbs.)  
1 opening ea. 5" x 10",  
1 opening ea. 10" x 10"



SN or ST 6 (Wt. 73 lbs.)  
6 openings ea. 5" x 5"



SN or ST 3A (Wt. 61 lbs.)  
3 openings ea. 5" x 10"



SN or ST 1 (Wt. 53 lbs.)  
1 opening ea. 15" x 10"



SN or ST Base (Wt. 15 lbs.)

## Pull-out Shelf

An optional pull-out shelf for the convenience in handling customers' bond boxes is available. The shelf is framed in heavy gauge steel, finished to match module. Surface of shelf, which extends 11 1/2", is stainless steel. A spacer section (dummy) the same height (1 1/2") as the shelf unit is available to be used alternatively on vertical sections to maintain equal stacking dimensions.



# BRIDGEMAN

**Bridgeman Security Equipment**

510 West Washington Blvd.  
Montebello, CA 90640  
(323) 724-5880 Telephone  
(800) 334-6060 Toll Free  
(213) 727-0236 Fax  
e-mail: [bridgeman@socalSAFE.com](mailto:bridgeman@socalSAFE.com)

All specifications subject to change without notice.  
All cases are furnished with bond boxes, number plates and locks with keys ready for use.  
All dimensions indicated for the drawings are for outside measurements only.  
©1993 Bridgeman Security Equipment.