



- NOTES:
1. ALL EXPOSED DOOR & VESTIBULE SURFACES FINISHED IN STAINLESS STEEL.
 2. SECURITY BARRIER FOR DOOR AND VESTIBULE ARE CONSTRUCTED OF FIBER REINFORCED CONCRETE.
 3. DESIGNED, MANUFACTURED AND TESTED IN ACCORDANCE WITH UL STANDARD UL608 (CERTIFICATION BP6254).
 4. STANDARD DAYGATE IS CONSTRUCTED OF CLEAR ANODIZED EXTRUDED ALUMINUM PROFILES AND GRAY ACRYLIC SHEET WITH ADA COMPLIANT LEVER LOCK SET IN US26D FINISH.
 5. VESTIBULE IS DESIGNED FOR GROUTLESS INSTALL. IT IS TO BE WELDED TO MODULAR VAULT PANELS 1" WELD EVERY 12" MINIMUM. FULL WELD IS RECOMMENDED.
 6. SHIPPING WEIGHT IS 4,400 LBS.
 7. VESTIBULE IS CAST WITH TWO LIFT POINTS AT END. REQUEST (P/N 9040-0002) 3/4" T-12 LIFTING SWIVEL AND (P/N 9040-0006) 3/4"x4" COIL BOLT FOR PROPER RIGGING ATTACHMENT.
 8. VAULT DOOR REQUIRES INSTALL KIT FOR PROPER INSTALLATION. REQUEST KIT P/N 102-2200.

DO NOT SCALE



CAUTION!
ONLY PROFESSIONALS EXPERIENCED AND QUALIFIED IN THE INSTALLATION OF MODULAR VAULTS AND VAULT DOORS SHOULD INSTALL THIS PRODUCT.

American Vault.us

PRODUCT APPLICATION DRAWING
 100 SERIES VAULT DOOR CLASS 2
 MOD 102-01 LS SHOWN/MOD 102-02 RS OPP

SIZE	DWG NO	DATE	SHEET
B	20086	01.01.2012	1 OF 1