

ProCash 2350xe

Automated Teller Machine

Full-function ATM for outdoor use
Free-standing island drive-up system



The ProCash 2350xe has a modular design and is easy and fast to service – critical requirements especially for outdoor drive-up installations. Highly specialized durable materials ensure that the ProCash 2350xe will withstand vandalism and all forms of climate conditions.

The ProCash 2350xe is a full function, free-standing frontload system. Its climate control unit and rugged design make the ProCash 2350xe ideal for harsh outdoor environments.

The ProCash 2350xe is the latest addition to the ProCash product family, rounding off Wincor Nixdorf's line of solutions for drive-up banking. At the same time it is a system from the new generation of the ProCash product family that covers international customer requirements and trends. The flexibility of these systems is unrivaled on the market when it comes to ideal configuration and availability. The ProCash 2350xe has a modular design, and is easy and fast to service – critical requirements especially for outdoor drive-up installations.



■ Designed especially for operation from the secure and comfortable environment of a car, the ProCash 2350xe guarantees 7x24 hour service even in the most rugged environments. The ergonomic layout of all its elements allows easy use from all kinds of vehicles. The system can be customized to match the operator's individual branding.

ProCash 2350xe ATM

TECHNICAL DATA

Features and highlights:

- Made of highly specialized durable materials with a universal UL-listed acrylic-coated housing
- Climate control unit includes air conditioning as standard
- Frontload system with modular design for ease and speed of serviceability
- Fits standard 42" islands
- Individual color customization option supports individual branding
- Standard equipment includes Pentium PC
- 12.1" sunlight-readable LCD screen with autoscaling functionality as standard
- Issues bundles of up to 60 banknotes
- Lighted indicators at all input and output modules, labeling in Braille

In addition to its basic functions of dispensing cash and displaying information the ProCash 2350xe can be enhanced to meet a financial institution's specific requirements:

- Print receipts or other documents
- Issue tickets or vouchers from versatile cassettes
- Print statements/other information up to a paper width of 9.84" (250 mm)
- Deposit banknotes/valuable documents (envelope deposit)

Published by
Wincor Nixdorf International GmbH
Banking Division
Heinz-Nixdorf-Ring 1
D-33106 Paderborn
Germany
Phone +49 (0) 52 51/693 33 01
Fax +49 (0) 52 51/693 59 18
info.banking@wincor-nixdorf.com

<http://www.wincor-nixdorf.com>
© Wincor Nixdorf International GmbH
ProCash® is a registered trademark of Wincor Nixdorf International GmbH.
All rights, including rights created by patent grant or registration of a utility model or design, are reserved.
Delivery subject to availability, subject to change for technical reasons.

Order No.
Printed in Germany, May, 2004

SYSTEM CONTROL

Standard PC

DISPLAY

The various VGA, SVGA and XGA resolutions can be implemented on a single display thanks to the autoscaling function.

- 12.1" TFT LCD sunlight

DISPLAY OPTIONS

- Touchscreen
- Privacy display filter

KEYBOARD

- 8 softkeys made of stainless steel
- Numeric keypad including 4 function keys

KEYBOARD OPTIONS

- Encrypting PIN pad (EPP)
- Encryption/decryption module (EDM)

CARD HANDLING

- Hybrid card reader (motorized)
- EMV 2000-certified
- Tamperproof card slot
- Card retained if not removed
- Card returned in case of power failure

CARD HANDLING OPTIONS

- Different card retract boxes

CASH DISPENSING

- 1 to 4 cassettes (sealable as standard)
- Max. filling height per cassette: 12.20" (310 mm)
- Single reject/bundle retract, storage in separate compartments

CASH DISPENSING OPTIONS

- Cassette with lock
- Cassette with low cash sensor
- Cassette pre-setting

SECURITY

- Safe UL 291 Level 1

SECURITY OPTIONS

- Intruder alarm system
- Portrait camera
- Uninterruptible power supply

OPTIONS

PRINTERS

- Receipt printer (dot matrix or thermal)
- Journal printer (dot matrix or thermal)
- Statement/information printer (dot matrix or thermal)

ENVELOPE DEPOSIT

- Integrated envelope dispenser
- Single line printing of transaction data
- Capacity: up to 200 or 300 envelopes, depending on the deposit box, special security box as an option

MISCELLANEOUS

- Lighted logo area
- Lighted indicators at all input and output modules
- Info panel for card symbols
- Audio functionality, headset plug
- Climate control unit, air conditioning as standard

OPERATING SYSTEM

- Windows NT
- Windows XP

APPLICATION SOFTWARE

- ProClassic
- IBM 473x/PBM Emulation
- NDC (NCR Direct Connect)
- DDC (Diebold Direct Connect)

POWER SUPPLY

110 – 120 V~/220 – 240 V~, 50 – 60 Hz

ENVIRONMENTAL

Temperature range

- -30° F to 122° F (-35° C to 50° C)

Relative humidity

- 5% to 85%

APPROVALS

